



# F4C

## ROTARY TILLER

Machinery composed by a tilling rotor, complete with blades rotating in the tractor forwarding direction and a rear hood for soil containing. The working depth can be adjusted by lateral skids, wheels, rollers or rear bed former hoods. Our rotary tillers achieve very high-level of soil tilling, even in presence of weed, cultural residues and very tough fields. Therefore, they are suitable for primary as for secondary soil preparation. The horizontal tilling rotor, available in various diameters, can fit different types of blades, in relation to the soil natural conditions and working procedures.



HP 70-140



CM 28 | INCH 11

- **Universal 3-point linkage Cat. 2**
- Lateral transmission driven by chain in oil bath
- **Multi-speed gearbox 540 - 750 - 1000 rpm PTO**
- Automatic spring-loaded chain tensioner
- **Front dual metal face seals in oil bath on rotors**
- 6x standard "C" blades per flange
- **Pair of adjustable lateral skids for working depth regulation**
- Cardan shaft with shear bolt torque limiter SB type (1"3/8 Z=6 tractor side yoke)
- **Swinging arms tractor coupling**
- Removable flanged rotor with blades facing outwards

Model	Working width		Total Width		Blades	Weight		Price
	cm	inch	cm	inch		kg	lbs	
F4C-210	210	83	227	89	48	715	1576	19,430 +GST
F4C-230	230	91	247	97	54	755	1664	19,640 +GST
F4C-250	250	98	267	105	60	790	1742	20,290 +GST
F4C-280	280	110	297	117	66	840	1852	21,060 +GST
F4C-300	300	118	317	125	72	880	1940	22,310 +GST

The weight refers to machine equipped with hood and skids

### OPTIONAL:

L shaped blades (instead of C blades) = \$235 + GST

Side blades facing inwards = \$291 + GST

Wearing steel protection counter-flanges = \$875 + GST

Upgrade for cardan shaft with automatic torque limiter SC type = \$1025 + GST

\*Tractor Culture reserves the right to adjust pricing based on exchange rate, & shipping cost.



TractorCulture